


Certifications - RLX-FHES



II 3 G EEx nC IIC
DEMKO 04 ATEX 04137473U



LISTED 62XN Class I
Division 2 Groups A, B, C & D
RADIO DEVICE FOR
HAZARDOUS LOCATIONS



0336 ⓘ
Ambient: $40^{\circ}\text{C} \leq T_a \leq 75^{\circ}\text{C}$
Temp. Code: T4A
6 to 28 Volts DC
6 Watts

RadioLinX Frequency Hopping Ethernet with Serial Device Server RLX-FHES

How to Contact Us: Sales and Support

All ProSoft Technology products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com
Languages spoken include: Chinese, Japanese, English

Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com
Languages spoken include: French, English

North America

+1.661.716.5100, support@prosoft-technology.com
Languages spoken include: English, Spanish

Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com
Languages spoken include: Spanish, English

Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com
Languages spoken include: Portuguese, English

RadioLinX Frequency Hopping Ethernet with Serial Device Server

RLX-FHES

The RadioLinX Frequency Hopping Ethernet with Serial Device Server contains an embedded serial device server that enables a transparent connection between an Ethernet host and a serial only device connected to the RLX-FHES RS-232 serial port. Virtually any serial protocol is supported including DF1, ASCII, DNP3, and Modbus RTU.

Encapsulated serial or Modbus/TCP Ethernet packets are delivered to the RLX-FHES socket where the serial server extracts the serial data stream from the Ethernet packets and outputs it to the RS-232 port. Bi-directional serial communication is supported by encapsulating the RS-232 port input stream into Ethernet packets, then sending them to the host client via the established socket interface.

Features and Benefits

Encapsulated serial or Modbus/TCP Ethernet packets are delivered to the RLX-FHES socket where the serial server extracts the serial data stream from the Ethernet packets and outputs it to the RS-232 port. Bi-directional serial communication is supported by encapsulating the RS-232 port input stream into Ethernet packets, then sending them to the host client via the established socket interface.

- Supports up to 1000 addressed devices with 2000 radios and 78 repeaters per network
- 64 user-selectable data channels for multiple network operation
- Full-Duplex asynchronous communication rates to 100 Kbps
- Active antenna diversity
- 2.4 GHz frequency hopping spread spectrum (FHSS) technology
- Secure wireless communications with data encryption, proprietary radio protocol, and 2.4 GHz FHSS physical layer
- Industrial temperature range
- 15+ mile (24 km) range with high-gain antennas (longer with repeaters)
- Remote diagnostics without interrupting data communications

- Over air user programmability (after initial configuration) using Windows-based software
- Three year standard warranty

Specifications

Radio

Frequency	2400 to 2483.5 MHz (varies by country)
Compliance	IEEE 802.3, 802.3u, 802.3x
Protocols	All standard IEEE 802.3 protocols
Encryption	ARC4 (40 or 128 bit)
Network Topology	Peer-to-Peer, store and forward repeater
Hop Patterns	64 independent, non-interfacing networks
Error Detection	32-bit CRC and ARQ (Automatic Re-Send Query)
Radio Type	Frequency Hopping Spread Spectrum
Output power	1mW to 250mW, programmable (varies by country)
Channel data rates	250 Kbps
Receiver sensitivity	-96 dBm @ 10 ⁻⁶ BER
Channels - user selectable	79 North America (varies by country)
Typical indoor range	500 to 1500 ft (150 to 450 meters)
Outdoor range	15 + miles line of site with high-gain antennas
Security	ARC4 (40 or 128 bit)

Physical

Enclosure	Extruded aluminum with DIN and panel mount
Size	4.10" x 3.71" x 2.05" (104.1 mm x 94.23 mm x 52.07 mm)
Vibration	IEC 60068-2-6
Shock	IEC 60068-2-27
Serial Data Port	RS-232, DB-9 Asynchronous half-duplex/full-duplex 2400 bps to 115.2 Kbps full duplex
Ethernet port	10/100 Base-T connector, shielded RJ45 IEEE 802.3, 802.3u, 802.3x
Antenna ports	(2) RP-SMA connectors, automatic antenna diversity
Weight	1 lbs /454g

Environmental

Operating temperature	-40°C to +70°C (-40° F to 158° F)
Humidity	To 90% RH, non-condensing
External power	10 to 24 VDC
Average power	<4W

Regulatory Approvals

Type Approvals

FCC	FCC Part 15.247
Industry Canada	RSS 210
Europe / CE	LVD EN 50850-2000 RF Safety EN 50364-2001 EMC EN 301 489-1, EN 301 489-17 Spectrum EN 300 328 v1.4.1
Mexico	Nom 121 SCT1 2 or 1
Australia	AS/NZS 4771
Brazil	365 / 2004 e 238 / 2000
Malaysia	SIRIM

Hazardous Locations

UL	UL 1604 Class 1 Division 2, Groups A, B, C, D Temp Code T4A
CSA/cUL	C22.2 No. 213-1987
ATEX Zone 2	ATEX II 3 G EEx nC IIC

Visit our web site for the latest certification information.

Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

Ordering Information

Use the following Ordering Information to identify the radio product needed for your region. If you are unsure which radio to select, please contact your local distributor.

RadioLinx 2.4 GHz Wireless Ethernet Switches (FHE, FHS, and FHES)

Country	Catalog #	Frequency
Australia	RLX-FHxx-AU	2400 to 2483.5 MHz
Brazil	RLX-FHxx-US	2400 to 2483.5 MHz
China	RLX-FHxx-CN	2400 to 2483.5 MHz
Europe	RLX-FHxx-EU	2400 to 2483.5 MHz
France	RLX-FHxx-FR	2400 to 2454 MHz
India	RLX-FHxx-UK	2400 to 2483.5 MHz
Malaysia	RLX-FHxx-UK	2400 to 2483.5 MHz
Mexico	RLX-FHxx-MX	2450 to 2483.5 MHz

Country	Catalog #	Frequency
Saudi Arabia	RLX-FHxx-SA	2413 to 2439 MHz
Singapore	RLX-FHxx-SG	2400 to 2483.5 MHz
South Africa	RLX-FHxx-EU	2400 to 2483.5 MHz
South Korea	RLX-FHxx-EU	2400 to 2483.5 MHz
United Kingdom	RLX-FHxx-UK	2400 to 2483.5 MHz
USA	RLX-FHxx-US	2400 to 2483.5 MHz
Venezuela	RLX-FHxx-VE	2400 to 2483.5 MHz

Country	RF Power	Power Supply
Australia	4W	AU
Brazil	4W	US
China	500 mW EIRP	EU
Europe	100 mW EIRP	EU
France	100 mW EIRP	EU
India	100 mW EIRP	UK
Malaysia	100 mW EIRP	UK
Mexico	650 mW EIRP	US
Saudi Arabia	100 mW EIRP	US
Singapore	100 mW EIRP	UK
South Africa	100 mW EIRP	EU
South Korea	100 mW EIRP	EU
United Kingdom	100 mW EIRP	UK
USA	4W	US
Venezuela	4W	US